


## POP 4 255 C32 (900 766)


- Effective protection against mains-frequency surges
- Compact design allows easy retrofitting
- Compliance with EN 5055



Figure without obligation



Basic circuit diagram POP 4 255 C32



Dimension drawing POP 4 255 C32

### POP+MCB

Type Part No.	POP 4 255 C32 900 766
Power supply system	three-phase TT / TN system
Number of poles	3P + N
Nominal a.c. voltage ( $U_N$ )	230 / 400 V
Nominal frequency ( $f_N$ )	50 Hz
Operating temperature range ( $T_U$ )	-25 °C ... +60 °C
Cross-sectional area (L1, L2, L3, N) (min.)	2.5 mm <sup>2</sup> solid / flexible
Cross-sectional area (L1, L2, L3, N) (max.)	16 mm <sup>2</sup> flexible / 25 mm <sup>2</sup> stranded
Degree of protection protection	IP 20
Capacity	5 module(s), DIN 43880
Mounting	35 mm DIN rails acc. to EN 60715

### POP

Type Part No.	POP 4 255 C32 900 766
Tested to	EN 50550
Max. non-tripping a.c. voltage	255 V
Max. tripping a.c. voltage	415 V
Tripping time at 275 V a.c.	8 s
Tripping time at 400 V a.c.	120 ms
Max. current at 275 V a.c.	0.4 A
Max. current at 400 V a.c.	0.6 A
Power consumption	0.7 VA
Trip indicator	red

### MCB

Type Part No.	POP 4 255 C32 900 766
Tripping characteristic	C
Nominal alternating current ( $I_n$ )	32 A
Rated switching capacity ( $I_{cn}$ ) acc. to EN 60898	6 kA
Weight	545 g
Customs tariff number	85363030
GTIN	4013364156173
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.