


## BXT ML4 BD EX 24 (920 381)


- For universal use, with LifeCheck monitoring function
- Self-capacitance and self-inductance negligibly small
- For installation in conformity with the lightning protection zone concept at the boundaries from  $0_B - 2$  and higher



Figure without obligation



Basic circuit diagram BXT ML4 BD EX 24



Dimension drawing BXT ML4 BD EX 24

Space-saving LifeCheck-equipped surge arrester module for protecting two pairs in intrinsically safe measuring circuits and bus systems, meets FISCO requirements. ATEX. Insulation strength > 500 V line-earth.

If LifeCheck detects thermal or electrical overload, the arrester has to be replaced. This status is indicated contactlessly by DEHNrecord LC / SCM / MCM.

Type	BXT ML4 BD EX 24
Part No.	920 381
SPD class	TYPE 2 <sup>Pi</sup>
SPD monitoring	LifeCheck
Nominal voltage ( $U_N$ )	24 V
Max. continuous operating voltage (d.c.) ( $U_c$ )	33 V
Max. continuous operating voltage (a.c.) ( $U_c$ )	23 V
Max. input voltage acc. to EN 60079-11 ( $U_i$ )	30 V
Max. input current acc. to EN 60079-11 ( $I_i$ )	0.5 A
D1 Total lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	4 kA
D1 Lightning impulse current (10/350 $\mu$ s) per line ( $I_{imp}$ )	1 kA
C2 Total nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	20 kA
C2 Nominal discharge current (8/20 $\mu$ s) per line ( $I_n$ )	5 kA
Voltage protection level line-line for $I_{imp}$ D1 ( $U_p$ )	$\leq 50$ V
Voltage protection level line-PG for $I_{imp}$ D1 ( $U_p$ )	$\leq 1300$ V
Voltage protection level line-line for $I_n$ C2 ( $U_p$ )	$\leq 52$ V
Voltage protection level line-PG for $I_n$ C2 ( $U_p$ )	$\leq 1400$ V
Voltage protection level line-line at 1 kV/ $\mu$ s C3 ( $U_p$ )	$\leq 45$ V
Voltage protection level line-PG at 1 kV/ $\mu$ s C3 ( $U_p$ )	$\leq 1100$ V
Series resistance per line	1.0 ohm
Cut-off frequency line-line ( $f_c$ )	7.7 MHz
Capacitance line-line (C)	$\leq 0.8$ nF
Capacitance line-PG (C)	$\leq 16$ pF
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Degree of protection (with plugged-in protection module)	IP 20
Plugs into	base part
Earthing via	base part
Enclosure material	polyamide PA 6.6
Colour	blue
Test standards	IEC 61643-21 / EN 61643-21, UL 497B
Approvals <sup>1)</sup>	CSA, EACEx, ATEX, IECEx, CSA & USA Hazloc, SIL
SIL classification	up to SIL3 <sup>*)</sup>
ATEX approvals (1)	KEMA 06ATEX0274 X: II 2 (1) G Ex ia [ia Ga] IIC T4 ... T6 Gb
ATEX approvals (2)	KEMA 06ATEX0274 X: II 2 G Ex ib IIC T4 ... T6 Gb
IECEx approvals (1)	DEK 11.0078X: Ex ia [ia Ga] IIC T4 ... T6 Gb
IECEx approvals (2)	DEK 11.0078X: Ex ib IIC T4 ... T6 Gb
CSA & USA Hazloc approvals (1)	70000011: Class I Div. 1; Class I Zone 1
CSA & USA Hazloc approvals (2)	70000011: Ex ia [ia] IIC T4 ... T6
Weight	23 g
Customs tariff number	85363010
GTIN	4013364109025
PU	1 pc(s)

<sup>\*)</sup> For more detailed information, please visit [www.dehn-international.com](http://www.dehn-international.com).

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.