


## DG MP TNS ACI 275 FM (942 440)


- Prewired complete unit consisting of a base part and remote signalling contact connection with push-in connection system and plug-in protection modules
- ACI switch / spark gap combination integrated in the protection module
- High device reliability due to "Thermo Dynamic Control" arrester monitoring and ACI technology
- No backup protection device required due to ACI technology
- Smaller connection cross-section of 6 mm<sup>2</sup> always sufficient



Figure without obligation



Basic circuit diagram DG MP TNS ACI 275 FM



Dimensional drawing DG MP TNS ACI 275 FM

Modular surge arrester with Advanced Circuit Interruption (ACI) for TN-S systems.

Type	DG MP TNS ACI 275 FM
Part No.	942 440
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment ( $\leq 10$ m)	type 2 + type 3
Nominal a.c. voltage ( $U_N$ )	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage AC [L-PE] ( $U_C$ )	275 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [N-PE] ( $U_C$ )	255 V (50 / 60 Hz)
Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	20 kA
Nominal load current for "V-connection" ( $I_L$ )	40 A
Voltage protection level [L-PE] / [N-PE] ( $U_P$ )	$\leq 1.5$ / $\leq 1.5$ kV
Voltage protection level [L-PE] / [N-PE] at 5 kA ( $U_P$ )	$\leq 1.5$ / $\leq 1.5$ kV
Response time ( $t_A$ )	$\leq 100$ ns
Additional external fuse	no
Short-circuit withstand capability ( $I_{SCCR}$ )	25 kA <sub>rms</sub>
Max. mains-side overcurrent protection with "V-connection"	40 A gG
Max. mains-side overcurrent protection with stub wiring (double connection 2 x 10 mm <sup>2</sup> )	none
Temporary overvoltage (TOV) ( $U_T$ ) – Characteristic	335 V / 5 sec. – withstand
Temporary overvoltage (TOV) ( $U_T$ ) – Characteristic	440 V / 120 min. – withstand
Leakage current	no leakage current
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm <sup>2</sup> solid
Cross-sectional area (min.)	6 mm <sup>2</sup> flexible
Cross-sectional area (max.)	10 mm <sup>2</sup> solid / flexible
Cross-sectional area (min.) with wire end ferrule	1.5 mm <sup>2</sup>
Cross-sectional area (max.) with wire end ferrule	6 mm <sup>2</sup>
Cross-sectional area (max.) with wire end ferrule without collar	10 mm <sup>2</sup>
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA, VDE
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid / flexible
Weight	377 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364477148
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.