

APC 60 62 (785 758)



Figure without obligation

- Reinforced stand-up collar
- Zip and hook-and-loop fasteners

| Type | APC 60 62 |
|---|--|
| Part No. | 785 758 |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| Arc energy (W_{arc} or W_{LEP}) | 320 kJ |
| EuroTest PIP001 (10 kA / 1 s – three-pole) | Yes |
| Extended electric arc energy (W_{arc} or W_{LEP}) (based on box test) | 630 kJ |
| Arc Rating – ATPV (Open Arc Test) | 33.1 cal / cm ² |
| PPE category (NFPA 70E) | PPE 3 |
| Size (international) | 60 / 62 (XXL) |
| Outer material | Siliconised calf grain leather, 100% Kevlar interlock knit |
| Inner material | 100% cotton |
| Material (sewing thread) | 100% Kevlar |
| Standard | IEC 61482-2, EN ISO 14116 |
| Weight | 3,21 kg |
| Customs tariff number (Comb. Nomenclature EU) | 42031000 |
| GTIN | 4013364245150 |
| PU | 1 pc(s) |

In case of very heavy soiling, the protective coat can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.