

**APJ 58 (785 775)**



Figure without obligation

- Reinforced stand-up collar
- Useful side arm pockets

| Type  | APJ 58   |
|---|--|
| Part No.  | 785 775  |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole)            | APC 2  |
| Arc energy ( $W_{arc}$ or $W_{LEP}$ )                                       | 320 kJ   |
| EuroTest PIP001 (10 kA / 1 s – three-pole)                                  | Yes  |
| Extended electric arc energy ( $W_{arc}$ or $W_{LEP}$ ) (based on box test) | 630 kJ   |
| Arc Rating – ATPV (Open Arc Test)   | 33.1 cal / cm <sup>2</sup>                                 |
| PPE category (NFPA 70E)   | PPE 3  |
| Size (international)  | 58 (3XL)   |
| Outer material  | Siliconised calf grain leather, 100% Kevlar interlock knit |
| Inner material  | 100% cotton  |
| Material (sewing thread)  | 100% Kevlar  |
| Standard  | IEC 61482-2, EN ISO 14116                                  |
| Weight  | 2,01 kg  |
| Customs tariff number (Comb. Nomenclature EU)                               | 42031000   |
| GTIN  | 4013364149519  |
| PU  | 1 pc(s)  |

<sup>1)</sup> The distance of the specimen was reduced from 300 mm to 150 mm based on IEC 61482-1-2.  
 In case of very heavy soiling, the protective jacket can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.