

APT 48 (785 780)



Figure without obligation

- Knee pads and pair of braces included
- Pockets for knee pads
- Adjustable belt

Type Part No.	APT 48 785 780
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LBP})	320 kJ
Extended electric arc energy (W_{arc} or W_{LBP}) (based on box test)	630 kJ
Arc Rating – ATPV (Open Arc Test)	29.2 cal / cm ²
PPE category (NFPA 70E)	PPE 3
Size (international)	48 (S)
Outer material	Siliconised calf grain leather, 100% Kevlar interlock knit
Inner material	100% cotton
Material (sewing thread)	100% Kevlar
Standard	IEC 61482-2, EN ISO 14116
Weight	1,46 kg
Customs tariff number (Comb. Nomenclature EU)	42031000
GTIN	4013364149526
PU	1 pc(s)

¹⁾ The distance of the specimen was reduced from 300 mm to 150 mm based on IEC 61482-1-2.
 In case of very heavy soiling, the protective trousers can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.