

**NEW APUP M (787 023)**



Figure without obligation

| Type  | APUP M  |
|---|---|
| Part No.  | 787 023 <small>new</small>  |
| Arc fault protection class (box test 4 kA/0.5 s – single-pole)  | APC 1   |
| Arc power ( $W_{arc}$ or $W_{LBP}$ )                            | 168 kJ  |
| Arc Rating – ATPV (Open Arc Test)                               | 4.1 cal / cm <sup>2</sup>   |
| In combination with DEHNcare ArcFit Indoor                      | 31 cal / cm <sup>2</sup>  |
| In combination with DEHNcare ArcFit Outdoor                     | 37 cal / cm <sup>2</sup>  |
| Arc Rating – ELIM (in combination with DEHNcare ArcFit Indoor)  | 28 cal / cm <sup>2</sup>  |
| Arc Rating – ELIM (in combination with DEHNcare ArcFit Outdoor) | 34 cal / cm <sup>2</sup>  |
| Standards   | IEC 61482-2, EN ISO 11612, EN 1149-5                                  |
| Material  | Cotton (50%), modacrylic (39%), viscose (10%), static inhibitors (1%) |
| Weight per unit area  | 160 g/m <sup>2</sup>  |
| Size (international)  | M   |
| Colour  | blue  |
| Weight  | 250 g   |
| Customs tariff number (Comb. Nomenclature EU)                   | 61034200  |
| GTIN  | 4013364482432   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.