

APD 63C S (787 380)



Figure without obligation

Type	APD 63C S
Part No.	787 380 (S)
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LBP})	320 kJ
Extended electric arc energy (W_{arc} or W_{LBP}) (based on box test)	630 kJ
Arc Rating – ATPV (Open Arc)	63 cal / cm ²
Arc Rating – ELIM (Open Arc)	58 cal / cm ²
PPE category (NFPA 70E)	PPE 4
Material – outer fabric	Modacrylic (46%), HT viscose (22%), FR viscose (18%), para-aramid (12%), static inhibitors (2%)
Material – lining / non-woven material	Lining: Aramid (34%), FR viscose (34%), Reg. viscose (32%) / non-woven material: FR viscose (85%), para-aramid (15%)
Outer fabric weight per unit area	225 g / m ²
Lining / non-woven material weight per unit area	430 g / m ²
Material (sewing thread)	Kevlar (100%)
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 13688, EN ISO 11611, EN 17353, ASTM F1959
Colour	navy blue
Zipper	red
Size (international)	48 (S)
Weight	1,1 kg
Customs tariff number (Comb. Nomenclature EU)	62034911
GTIN	4013364512399
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.