

SR D50 4700 FS2500 IP SA HVI GFK V2A (105 339)



Figure without obligation

Supporting tube with internal sealing end and EB spring element. Air-termination rod Ø22/16/10 mm.

Type	SR D50 4700 FS2500 IP SA HVI GFK V2A
Part No.	105 339
Material of air-termination rod	StSt
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / StSt
Length of supporting tube	4700 mm
Transport length	4700 mm
Outside diameter Ø	50 mm
Length of insulating clearance	1535 mm
Wall thickness	3 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	16,9 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364157897
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.