

SR D40 2400 FSP500 SA HVI LI PL GFK AL (105 677)



Figure without obligation

Supporting tube with internal sealing end and EB spring element. Air-termination tip Ø10#mm.

Type	SR D40 2400 FSP500 SA HVI LI PL GFK AL
Part No.	105 677
Material of air-termination tip	StSt
Length of air-termination tip	500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	2400 mm
Transport length	2400 mm
Outside diameter Ø	40 mm
Length of insulating clearance	1230 mm
Wall thickness	4 mm
Material factor km	0.7
Permanent temperature range	-50°C to +100°C
Type	UV-stabilised
Sleeve	50 x 5 mm
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Max. gust wind speed	See wind load pamphlet
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	3,3 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364500044
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Specifications regarding max. gust wind speeds of the air-termination systems can be found in the wind load matrix.