




AL ZF KB 6.10STTZN B5.2 6.5 L81 AL (377 100)



Figure without obligation



Arrangement:

| Type                                              | AL ZF KB 6.10STTZN B5.2 6.5 L81 AL                                                                                                                                       |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part No.                                          | 377 100                                                                                                                                                                  |
| Material of bracket                               | Al                                                                                                                                                                       |
| Material thickness (t1)                           | 3 mm                                                                                                                                                                     |
| Fixing                                            | [4x] Ø5.2 / [2x] Ø6.5 mm                                                                                                                                                 |
| Fixing possibility                                | blind rivets or drilling screws                                                                                                                                          |
| Application note                                  | according to EN 62305-3 Suppl. 1 4 rivets Ø5mm, 2 rivets Ø6mm shall be used to connect materials ≥ 0.5mm thick or 2 Parker screws StSt Ø6.3mm for materials ≥ 2mm thick. |
| Material of clamping piece                        | St/tZn                                                                                                                                                                   |
| Screw                                             | M10 x 30 mm                                                                                                                                                              |
| Material of screw / nut                           | StSt                                                                                                                                                                     |
| Connection                                        | lengthwise / crosswise                                                                                                                                                   |
| Connection with                                   | clamping piece                                                                                                                                                           |
| Clamping range Rd                                 | 6-10 mm                                                                                                                                                                  |
| Lightning current carrying capability (10/350 µs) | 50 kA <sup>*)</sup>                                                                                                                                                      |
| Standard                                          | EN 62561-1                                                                                                                                                               |
| Weight                                            | 74 g                                                                                                                                                                     |
| Customs tariff number (Comb. Nomenclature EU)     | 85359000                                                                                                                                                                 |
| GTIN                                              | 4013364078604                                                                                                                                                            |
| PU                                                | 50 pc(s)                                                                                                                                                                 |

\*) For exact assignment, see test certificate.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.