

HVI LO 75 20 L100M SW M (819 135)



Figure without obligation

The HVI long Conductor for on-site assembly is delivered in a length of 100 m on a disposable plywood reel (diameter approx. 800 mm, width approx. 485 mm), incl. an Allen key.

| Type                                                              | HVI LO 75 20 L100M SW M               |
|-------------------------------------------------------------------|---------------------------------------|
| Part No.                                                          | 819 135                               |
| Material of conductor                                             | Cu                                    |
| Material of insulation                                            | PE                                    |
| Material of sheath                                                | PE                                    |
| Colour of conductor                                               | black •                               |
| Colour RAL                                                        | similar to 9011                       |
| Cross section of core (stranded)                                  | 19 mm²                                |
| Lightning current carrying capability (class / I <sub>imp</sub> ) | H1 / 150 kA                           |
| Equivalent separation distance s (in air)                         | ≤ 75 cm                               |
| Diameter Ø conductor                                              | 20 mm                                 |
| Coating characteristics                                           | UV-stabilised and weather-resistant   |
| Standard                                                          | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight                                                            | 488 g/m                               |
| Customs tariff number (Comb. Nomenclature EU)                     | 85446010                              |
| GTIN                                                              | 4013364141759                         |
| PU                                                                | 100 m                                 |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.