


HVI 23 L6M SR3200 IP FSP1000 GFK AL (819 336)



Figure without obligation



With interanl sealing end and air-termination tip StSt Ø10 mm, length 1000 mm.

Type	HVI 23 L6M SR3200 IP FSP1000 GFK AL
Part No.	819 336
Material of air-termination tip	StSt
Length of air-termination tip	1000 mm
Material of supporting tube	GRP / Al
Length of supporting tube	3200 mm
Transport length	3200 mm
Outside diameter Ø	50 mm
Diameter Ø conductor	23 mm
Colour of conductor	grey
Material of conductor	Cu
RAL colour	similar to 7035
Cross-section of core (stranded)	19 mm ²
Lightning current carrying capability (class / I _{imp})	H1 / 150 kA
Equivalent separation distance s (in air)	≤ 75 cm
Material of insulation	PE
Material of sheath	PE
Material characteristics	UV stabilised and weather resistant
Connection diameter	10 mm
Material of connection elements	StSt
Supporting tube	50 x 4 mm
Minimum order length	6 m
Max. free length with air-termination tip (wall mounting)	3500 mm
Max. gust wind speed	(Max. free length 3,500 mm, 1x HVI grey inside) 237 km/h
Max. gust wind speed	(Max. free length 3,500 mm, 1x HVI grey outside) 225 km/h
Max. gust wind speed	(Max. free length 3,500 mm, 4x HVI grey outside) 194 km/h
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	9,6 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364241237
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The conductor cannot be returned as it is made to order.