

POP+RU+MCB+SPD 32A 1P+N (900 725)

- Complete protection against transient and power frequency overvoltages
- Compact design allows easy retrofitting
- Meets the requirements of EN 61643-11 (SPD) and EN 63052 (POP)
- Reclosing Unit for automatic reconnection



Figure without obligation

Dimension drawing POP+RU+MCB+SPD 32A 1P+N

The article will be available shortly.

General

Type	POP+RU+MCB+SPD 32A 1P+N
Part No.	900 725 NEW
Tightening torque	4 Nm
Cross-sectional area (min.)	2.5 mm ² solid / fine-stranded
Cross-sectional area (max.)	35 mm ² stranded / 25 mm ² fine-stranded
Degree of protection	IP 20
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	Thermoplastic, grey, UL 94 V-0
Operating temperature range	-25°C to +60°C
Installation point	Indoor
Approvals	CE
Dimensions	4 Standard DIN module, DIN 43880

SPD

Type	POP+RU+MCB+SPD 32A 1P+N
Part No.	900 725 NEW
SPD according to EN 61643-11 / ... IEC 61643-11	Type 2 / class II
Max. continuous operating voltage (a.c.) [L-N] (U _c)	275 V
Max. continuous operating voltage (a.c.) [N-PE] (U _c)	255 V
Max. discharge current (8/20 μs) [L-N] (I _{max})	15 kA
Max. discharge current (8/20 μs) [N-PE] (I _{max})	20 kA
Nominal discharge current (8/20 μs) [L-N] (I _n)	5 kA
Nominal discharge current (8/20 μs) [N-PE] (I _n)	10 kA
Voltage protection level [L-N] (U _p)	1.5 kV
Voltage protection level [N-PE] (U _p)	1.5 kV
Short-circuit withstand capability (I _{scCR})	50 kA
Response time [L-N] (t _A)	25 ns
Response time [N-PE] (t _A)	100 ns
Visual indication of end of service life	Yes
Dynamic thermal shutdown (L-N) (U _T)	Yes

POP

Type	POP+RU+MCB+SPD 32A 1P+N
Part No.	900 725 
Tested to	IEC EN 63052:2021-08
Nominal AC voltage [L-N] (U_N)	230 V
Nominal AC voltage [L-L] (U_N)	400 V
Maximum tripping time [$U_a = 255$ V] (t_A)	No tripping
Minimum non-tripping time [$U_a = 255$ V] (t_A)	No tripping
Maximum tripping time [$U_a = 275$ V] (t_A)	15 sec.
Minimum non-tripping time [$U_a = 275$ V] (t_A)	3 sec.
Maximum tripping time [$U_a = 300$ V] (t_A)	5 sec.
Minimum non-tripping time [$U_a = 300$ V] (t_A)	1 sec.
Maximum tripping time [$U_a = 350$ V] (t_A)	0.75 sec.
Minimum non-tripping time [$U_a = 350$ V] (t_A)	0.25 sec.
Maximum tripping time [$U_a = 400$ V] (t_A)	0.2 sec.
Minimum non-tripping time [$U_a = 400$ V] (t_A)	0.07 sec.

MCB

Type	POP+RU+MCB+SPD 32A 1P+N
Part No.	900 725 
Tested to	EN 60898, EN 60947-2
Tripping characteristic	C
Rated switching capacity (I_{cn}) acc. to EN 60898	6 kA
Rated switching capacity (I_{cn}) acc. to EN 60947-2	10 kA
Nominal AC voltage (U_N)	230 / 400 V
Nominal frequency (f_N)	50 / 60 Hz
Version	1 + N
Nominal alternating current (I_L)	32 A
Energy limitation class	3
Rated impulse withstand voltage	6.2 kV
Electromechanical service life	20,000 cycles
Contact position indication	Yes
Contact position indication	Yes (green / red)

RU

Type	POP+RU+MCB+SPD 32A 1P+N
Part No.	900 725 
In accordance with	EN 63024
Surge protection value (tripping)	280 V +/- 10 V
Surge return voltage	240 V +/- 10 V
Surge recovery times	5–10 sec.
Undervoltage protection value (tripping)	160 V +/- 10 V
Undervoltage return voltage	190 V +/- 10 V
Undervoltage recovery time	5–10 sec.
1 LED indication (separate from SPD)	Undervoltage/overvoltage (red), OK (green)
Dielectric strength	2,500 V AC for 1 minute
Lightning impulse voltage (U_{imp})	4 kV
Weight	456 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364559318
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.