

Double receptacle Cepex

Part number: 4404



MENNEKES

Elektrotechnik GmbH & Co. KG
Aloys-Mennekes-Straße 1
57399 KIRCHHUNDEM GERMANY
www.MENNEKES.org

Product Description

- screw connection technology
- 2 CEE-receptacles 16A 5p 6h 400V
- further variants on request

Technical Details

Double receptacle - Cepex		4404
Product serie		Cepex
Information receptacle 1		
Ampere		16A
Number of poles		5p
Clock position		6h
Nominal voltage AC		400V
Tightening torque connection terminal		1,2 Nm
Strip length solid conductor		8 - 10 mm
Conductor cross-section min.		1,5 mm ²
Conductor cross-section max.		4 mm ²
Information receptacle 2		
Ampere		16A
Number of poles		5p
Clock position		6h
Nominal voltage AC		400V
Tightening torque connection terminal		1,2 Nm
Strip length solid conductor		8 - 10 mm
Conductor cross-section min.		1,5 mm ²

Conductor cross-section max.	4 mm ²
General information	
Nominal frequency	50 - 60 Hz
Protection type IP	IP54
Contact carrier	standard
X-CONTACT	no
Connection	screw terminals
Contact screw drive	PZ2, slot
Pilot contact	no
Cable entry at the top	1 x M20x1,5
Blind cable entry at the rear	no
Enclosure base can be turned 180°	yes
Insertion direction	straight
Type of mounting	internal fixing
Highly resistant to chemicals	no
Military version	no
Lockable	no
Labeling field	no
IK code	IK08
Weight (net)	582 g
Packaging unit	4 pcs
Quantity per pallet	360 pcs
EAN / identification number	4015394315773

Permissible ambient conditions

Permanent ambient temperature	-5 °C to +40 °C
Max. average temperature over 24 hours	+35 °C

Material properties

Upper part	PC/ASA light grey [similar RAL 7035]
Base	PC light grey [similar RAL 7035]
Hinged lid	PC/ASA light grey [similar RAL 7035]

Material resistance

The material resistance overview can be found on the website in the section "Knowledge" - "Product knowledge" - "Materials"

Material and environmental properties

RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓

Regulations and Standards

Norm	DIN EN IEC 60309-2
Declaration of Conformity	CE

Dimensional Drawing

Drawing
1 MB 749
Dim. in mm

